

Kogellager enkele rij 400-59V-NICE - 400-59V-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/400-59v-nice>



- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	59V	2.000 0.000 50.80	3.375 85.73	0.937 23.80	0.937 23.80	21	3/8 9.53

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
1.35 0.61	2100 9345	1458 6488	1010 4455	817 3638	567 2523	396 1762

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560205
Binnendiameter	50.8 mm
Buitendiameter	85.73 mm
Dikte	23.8 mm
Gewicht	610 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE