


Kogellager enkele rij 5881-V-NICE - 5881-V-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/5881-v-nice>

5000 Series® Single Row Uground Flanged Radial Bearings

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5881™	V	+0.005/-0.000 +13/-00	+0.005/-0.000 +18/-00	+0.010/-0.010 +25/-25	0.062 1.57	1.500 38.10	0.125 3.18	+0.010/-0.010 +25/-25
		0.500 12.70	1.379 34.93	0.463 11.76				0.546 13.87

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY							
		REVOLUTIONS PER MINUTE							
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)		
16	3/16	0.12 4.75	0.08 0.08	375 1669	261 1181	160 803	145 648	101 449	71 316

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560267
Binnendiameter	12.7 mm
Buitendiameter	34.93 mm
2e Buitendiameter	38.1 mm
Dikte	11.76 mm
2e Dikte	13.87 mm
Gewicht	50 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE