

# Kogellager enkele rij 618-V-NICE - 618-V-NICE

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/618-v-nice>

**600** Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE



BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
618™	V	+0.010-0.000 +0.254-0.000	+0.010 +0.254	+0.010 +0.254	+0.010 +0.254	23	0.45 0.20
		1.375 34.92	1.406 35.93	2.1502 62.71	0.25 15.88	14 6.35	0.45 0.20

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10	50	100	250	500	1000
(lbs)	(lbs)	(lbs)	(lbs)	(lbs)	(lbs)
(N)	(N)	(N)	(N)	(N)	(N)
1794	1449	1089	579	419	298
7980	6442	4755	2578	1884	1328

Notes: Balls - Carbon Steel Grade 52100, Bands - Carbon Steel Soft, Bearings Oiled with a Rust Preventative, Washers - Carbon Steel Case Hard, All Bearings Marked on Band with "Designation Nice USA" as Shown

## PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560502
Binnendiameter	34.92 mm
Buitendiameter	62.71 mm
Dikte	15.88 mm
Gewicht	200 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE