

Lagerbloken toebehoren 7615-DL-NICE - 7615-DL-NICE

<https://www.123kogellager.be/kogellager-behuizing/lagerbloken/toebehoren/7615-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 8000 RPM
- THROUGH HOLES
- WATER WASH STAINLESS
- STEEL BEARING HOUSINGS
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION RESISTANCE AND EXCELLENT SEALING ARE REQUIRED

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005 Ø -0.013	+0.000 Ø0.00 -0.005	Ø0.00	0.0625 1.59	+0.005 +0.13 -0.005 -0.13
7615™ Ø	0.875 22.81	2.0506 52.83	0.6500 15.88		1.308 33.17	0.136 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (kg)
0.042 1.07	2.158 54.77	1.179 29.95	0.492 12.50	0.261 6.63	1/4-28	0.039 0.89	2970 13217	1350 6098	0.40 0.18

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
② Tolerance for 7613™ and larger is +0.0000/-0.0005 (+0.000/-0.015)
③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
④ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of NICE Bearings.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473462
Binnendiameter	23.81 mm
Buitendiameter	33.17 mm
Dikte	15.88 mm
Gewicht	180 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE