

Lagerbloken toebehoren 7618-DL-NICE - 7618-DL-NICE

<https://www.123kogellager.be/kogellager-behuizing/lagerbloken/toebehoren/7618-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 8000 RPM
- PRECISION MOUNTING
- SHOCK RESISTANT
- WATER CASE STANDARD
- SHOCK RESISTANT STANDARD
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED
- RECOMMENDED FOR APPLICATIONS WHERE EXACTLY SPECIFIED DIMENSIONS AND SUPERIOR QUALITY ARE REQUIRED

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005 Ø -0.013	+0.000 Ø0.00 -0.005			+0.005 +0.13 -0.005 -0.13
7618™ Ø	1.1250 28.58	2.5250 64.03	0.7500 19.05	0.0625 1.59	1.875 42.47	0.190 4.83

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT		
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (Db) (%)	Static C ₀ (Db) (%)	W (g) (kg)	
0.065 1.65	2.768 70.25	1.417 35.98	1.417 35.98	0.605 15.37	0.261 6.63	1/4-28 6.35	0.035 0.89	5360 23852	2620 11659	0.80 0.36

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
② Tolerance for 7613™ and larger is +0.0000/-0.0005 (+0.000/-0.015)
③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
④ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of NICE Bearings.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473493
Binnendiameter	28.58 mm
Buitendiameter	42.47 mm
Dikte	19.05 mm
Gewicht	360 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE