

Lagerbloken toebehoren 7620-DL-NICE - 7620-DL-NICE

<https://www.123kogellager.be/kogellager-behuizing/lagerbloken/toebehoren/7620-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 8000 RPM
- THROUGH HARDENED
- SHOCK RESISTANT
- WATER WASH RESISTANT
- STEEL BEARING STEEL
- SHARPLY ANGLED ANGULAR CONTACT BALLS
- AVAILABLE IN SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED
- RECOMMENDED FOR APPLICATIONS WHERE SHOCK, HEAT, VIBRATION AND EXPANDED LIFE ARE NECESSARY

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7620™	1.2500 31.75	2.5625 65.08	0.7500 19.05	0.0625 1.59	1.875 42.47	0.190 4.83

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (lb) (kg)
0.065 1.65	2.768 70.25	1.417 35.98	0.605 15.37	0.261 6.63	1/4-28	0.035 0.89	5360 23852	2620 11659	0.71 0.32

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
② Tolerance for 7613™ and larger is +.0000/-0.0006 (+.0001/-0.015)
③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
④ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of NICE Bearings.

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3616060473509
Binnendiameter	31.75 mm
Buitendiameter	42.47 mm
Dikte	19.05 mm
Gewicht	320 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE