


Lagerbloken toebehoren ER10-NICE - ER10-NICE

<https://www.123kogellager.be/kogellager-behuizing/lagerbloken/toebehoren/er10-nice>

ER Series Precision Ground Radial Bearings with **NICE**
Extended Inner Ring and Metric Outside Diameter

- EXCLUSIVE, HEAVY DUTY "N" BEALS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL YIELD GUARD AND INNER RING LATHEWORK PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN EXTREME ENVIRONMENTS
- OPTIONAL LIP FORMING SEAL IS AVAILABLE
- TWO LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO KNURLED OUP POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOSING UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK OXIDE FINISH PROVIDES ADDITIONAL RESISTANCE



PRINCIPLE DIMENSIONS													
BASIC BEARING NUMBER	SHAFT DIAMETER (mm)	OD (mm)	WIDTH (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	J (mm)	K (mm)	M (mm)	RADIUS (mm)
ER10	5/8	1.8504	1.732	13/32	1.318	31/64	1.764	9/64	3/64	3/32	3/16	5/8	0.040
	15.88	47	26.95	17.52	8.17	12.30	28.18	3.57	1.19	2.38	4.76	15.88	1.02

RADIAL CAPACITY											WEIGHT		
O (mm)	P (mm)	3-SET SCREWS	BASIC LOAD		REVOLUTIONS PER MINUTE							W (kg)	
			RATING C (N)	STATIC LOAD Co (N)	50	150	300	500	1200	1800	2500		5000
0.094	2.176	10-32	2893	1485	921	638	508	427	319	278	250	198	0.56
2.39	52.39		12527	6368	4098	2839	2292	1900	1420	1237	1113	881	0.25

ⓘ Shaft tolerance +.0002/-0.005 (+.002/-0.13) Ⓜ For low torque version add suffix "SFR"

PRODUCTKENMERKEN

Merk	NICE
N° Ean13	3663952560830
Binnendiameter	15.88 mm
Buitendiameter	28.18 mm
Dikte	15.88 mm
Gewicht	250 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE