


TSM Stangkop MXL-06-5-DUNLOP - MXL-06-5-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/tsm/mxl-06-5-dunlop>

MALE ROD ENDS **DUNLOP**



DUNLOP
MALE ROD ENDS

MX SERIES

Description:
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 40, heat treated to 85/90 tons/m² tensile, Phosphated all over.
Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M40, Heat Treated to 85/90 tons/m² tensile and Phosphated all over. **Balls:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MXL-06-5		.276	.237	.275	.437	.927	1.875	1.250	3/8 UNF	21	19410

Interchange table

Dunlop	Rose	NMB
MXL-M (Metric)	R02-M	R02-M
MX (Imperial)	R02	R02

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.
'0' in part number denotes grease nipple is fitted.

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060550873
Binnendiameter	7.937 mm
Buitendiameter	23.799 mm
Dikte	11.099 mm
Type	TSM
Draad	Rechtse draad
Smering	met
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE