


SI Stangkop FX-M10-C-DUNLOP - FX-M10-C-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/fx-m10-c-dunlop>

FEMALE ROD ENDS DUNLOP



FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 4J, heat treated to 50/50 tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M4J, heat treated to 50/50 tensile/ tensile axis Phosphated all over

Ball: Bearing Steel 100Cr6, Heat Treated and Phosphate all over

| Part No. Right Hand | Part No. Left Hand | B | W | H | O | D | F | A | J | M | X | Static Load Rating (Newtons) Radial |
|---------------------|--------------------|----|------|------|------|------|------|------|------|------------|----|-------------------------------------|
| FX-M10C | | 10 | 14.2 | 12.2 | 14.2 | 31.0 | 41.2 | 21.0 | 15.2 | M10 x 1.25 | 22 | 27460 |

Interchange table

| Dunlop | Rose | NMB |
|---------------|-------|-------|
| FX-M (metric) | RBJ-M | RBJ-M |
| FX (imperial) | RBJ | RBJ |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DUNLOP |
| N° Ean13 | 3616060555038 |
| Binnendiameter | 10 mm |
| Buitendiameter | 14.2 mm |
| Dikte | 12.2 mm |
| Type | SI |
| Draad | Rechtse draad |
| Smearing | met |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE