

SI Stangkop

FX-M10-DUNLOP - FX-M10-DUNLOP

https://www.123kogellager.be/kogellager-behuizing/stangkop/si/fx-m10-dunlop

FEMALE ROD ENDS



10MM Ø I.D.

10MM Ø I.D.

10MM Ø I.D.

FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: B17M 40, heat treated to 80/90 tons/in² tensile. Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C
Specification:
ELV & RoHS compliant

Housing: Forged B17M40, heat treated @ 80/90 tons/in² tensile/ all over

Ball: Bearing Steel 100Cr6, Heat Treated and Phosphate all over

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newtons) Radial
FX-M10		10	14.2	12.2	14.2	31.0	41.2	21.0	15.2	M10 x 1.50	22	27460

Interchange table

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060555045
Binnendiameter	10 mm
Buitendiameter	14.2 mm
Dikte	12.2 mm
Type	SI
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE