

SI Stangkop

FX-06-DUNLOP - FX-06-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/fx-06-dunlop>

FEMALE ROD ENDS



100MM 6UPT

100MM 6UPT

FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: B17M 40, heat treated to 80/90 tons/in² tensile. Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available.
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications.
Construction equipment.
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged B17M40, Heat Treated 80/90 tons/in² tensile and Phosphated all over.

Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No.	Part No.	B	W	H	O	D	F	A	J	M	X	Static Load Rating
Right Hand	Left Hand											Newton Radial
FX-06		3750	562	480	562	1.218	1.625	875	.600	3/8 UNF	22	27460

Interchange table

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060555250
Binnendiameter	3750 mm
Buitendiameter	562 mm
Dikte	480 mm
Type	SI
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE