



SI Stangkop FX-16-FG-DUNLOP - FX-16-FG-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/fx-16-fg-dunlop>

FEMALE ROD ENDS 



DESCRIPTION:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

MATERIAL SPECIFICATIONS:
Housing: 817M 40, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

FEATURES:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

POSSIBLE APPLICATIONS:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

TEMPERATURE RANGE:
-40°C to +150°C

SPECIFICATION:
ELV & RoHS compliant

Housing: Forged 817M40, Heat Treated 80/90 tons/in² tensile and Phosphated all over.

Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton) Radial
FX-16G		1.0000	1.375	1.0000	1.375	3.000	4.125	2.125	1.625	1 1/4 UNF	24	150250

Interchange table

Dunlop	Rose	NMB
FX-M (metric)	RBJ-M	RBJ-M
FX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060555328
Binnendiameter	10000 mm
Buitendiameter	1.375 mm
Dikte	1 mm
Type	SI
Draad	Rechtse draad
Smearing	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE