

SI Stangkop FSX-05-4-DUNLOP - FSX-05-4-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/fsx-05-4-dunlop>

FEMALE ROD ENDS



DESCRIPTION:
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

MATERIAL SPECIFICATIONS:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Strength PTFE Composite

TEMPERATURE RANGE:
-200°C to +240°C

FEATURES:
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

POSSIBLE APPLICATIONS:
Motorsport and heavy industrial mechanical applications.

SPECIFICATION:
ELV & RoHS compliant applications.

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-05-4		1/A	5/16 UNF	0.437	0.344	1.000	1.375	0.750	0.437	25500

Interchange table

Dunlop	Aurora	Fluro
FSX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060556301
Binnendiameter	6.35 mm
Buitendiameter	25.4 mm
Dikte	11.0998 mm
Type	SI
Draad	Rechtse draad
Smering	NA
Statische belasting	25.5 kN
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE