


SI Stangkop AL-SA-081-DUNLOP - AL-SA-081-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/si/al-sa-081-dunlop>

FEMALE ROD ENDS



AL SERIES

Description:
AL-Series is our 3-piece aluminium light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminium A6061, black anodised. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric bore & thread sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance
Light weight

Possible Applications:
Light industrial/mechanical applications
Weight restricted applications
Linear movement sensors

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Housing: Aluminium A6061, Black Anodised Race: GR-nylon, LV-3H
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-081		6	M6x1.00	7	6.75	19	30.0	13.5	7.3	11.6	7,720

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060556523
Binnendiameter	6 mm
Buitendiameter	9 mm
Dikte	6.75 mm
Type	SI
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE