



GE Stangkop GE100-FW-DUNLOP - GE100-FW-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge100-fw-dunlop>

SPHERICAL BEARINGS 



Outer Ring: Bearing Steel 100Cr6, Case Hardened

GE FW SERIES

Description:
GE-FW-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

Features:
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium-heavy industrial mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range:
-52°C to +121°C

Specification:
E.V. & RoHS compliant

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE100FW		100	85	95	160	3,075,000

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060557391
Binnendiameter	100 mm
Binnendiameter	3.937" inch
Buitendiameter	160 mm
Buitendiameter	6.299" inch
Dikte	85 mm
Dikte	3.346" inch
Type	GE
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE