

GE Stangkop

GE17-UK-2RS-DUNLOP - GE17-UK-2RS-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge17-uk-2rs-dunlop>

SPHERICAL BEARINGS 





GE UK SERIES

Description:
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.
Seals: Polyurethane.

Features
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications
Medium-heavy industrial mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control

Temperature Range
-200°C to +260°C
Specification
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened **Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Temperature PTFE Composite

| Part No. Unassembled | Part No. Sealed | Bore Size | W | H | D | Static Load Rating (Newtons) Radial |
|----------------------|-----------------|-----------|----|----|----|-------------------------------------|
| GE17UK-2RS | | 17 | 14 | 10 | 30 | 54,000 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | DUNLOP |
| N° Ean13 | 3616060558411 |
| Binnendiameter | 17 mm |
| Binnendiameter | 0.669" inch |
| Buitendiameter | 30 mm |
| Buitendiameter | 1.181" inch |
| Dikte | 14 mm |
| Dikte | 0.551" inch |
| Type | GE |
| Smering | met |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE