



GE Stangkop GE60-UK-DUNLOP - GE60-UK-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/ge/ge60-uk-dunlop>

SPHERICAL BEARINGS 

DUNLOP **GE UK SERIES**

SPHERICAL BEARINGS



Description:
GE-UK-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.
Seals: Polyurethane.

Features
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications
Medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range
-200°C to +240°C

Specification
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened Balls: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Temperature PTFE Composite

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE60UK		60	44	36	90	495,000

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060558602
Binnendiameter	60 mm
Buitendiameter	90 mm
Dikte	44 mm
Type	GE
Draad	Rechtse draad
Smering	met
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE