


SA Stangkop FSLX-M10-DUNLOP - FSLX-M10-DUNLOP

<https://www.123kogellager.be/kogellager-behuizing/stangkop/sa/fslx-m10-dunlop>

FEMALE ROD ENDS



FSLX SERIES

Description:
FSLX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate
Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C
Liner: High Strength PTFE Composite

Features:
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to +240°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specification:
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-M10		10	M10x1.50	10.50	28	43	20	17		34800

Temp Range: -200°C to +240°C

Interchange table

Dunlop	Aurora	Fluro
FSLX-M (Metric)	AW-M-T and AG-M-T	GUSW
FSLX (Imperial)	AW-T and AG-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCTKENMERKEN

Merk	DUNLOP
N° Ean13	3616060558855
Binnendiameter	10 mm
Buitendiameter	28 mm
Dikte	14 mm
Type	SA
Draad	Linkse draad
Smering	NA
Statische belasting	34.8 kN
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE