

Naaldhulslager BA2610-Z-IKO - BA2610-Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/ba2610-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed	Assembled inner ring
<i>P₀</i>	<i>D</i>	<i>C</i>	<i>d</i>	<i>H</i>	<i>J</i>	<i>C</i>	<i>C₀</i>	rpm		
41.275	1 5/8	2	15.88	A210	2.6					
			Max.	Max.	Min.	Max.	Min.	N	N	
								18900	30000	
								8000	2218	

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060601490
Binnendiameter	41.275 mm
Binnendiameter	1 5/8" inch
Buitendiameter	50.8 mm
Buitendiameter	2" inch
Dikte	15.88 mm
Dikte	5/8" inch
Grenstoerental	8000 rpm
Dynamische belasting	18.9 kN
Statische belasting	30 kN
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE