

Zelfklevend EA-9455-200ML-LOCTITE - EA-9455-200ML-LOCTITE

<https://www.123kogellager.be/lijm-smering/lijm/zelfklevend/ea-9455-200ml-loctite>

TITRE	Epoxy
DESCRIPTION	Epoxy bicomposant clair et souple, non coulant, ratio 1/1, 5 minutes
NOM	LOCTITE EA 9455
CONDITIONNEMENT	Ca. 2K 200 ml
DANGEROUS GOODS	Yes
COMMENTAIRE	-
APPROBATION	-

Description

LOCTITE® EA 9455 is a 2-part, clear, colorless, low viscosity, high strength, fast-curing, toughened, low viscosity, industrial grade liquid epoxy adhesive containing mercaptan. It is ideal for bonding and potting of optical components like sensors and lenses. It cures at room temperature after mixing. Key substrates include plastics, metals, glass, wood, ceramics and rubbers.

Avantages

Tough
Excellent electrical insulator
Low shrinkage properties
Ultra clear adhesive bondline
Good peel resistance
Mix ratio Resin: Hardener (by weight) 100 : 105, (by volume) 1 : 1
Key substrates include plastics, metals, glass, wood, ceramics and rubbers

Caractéristiques

2-part, clear, colorless, low viscosity, high strength, fast-curing, toughened, low viscosity, industrial grade liquid epoxy adhesive.

PRODUCTKENMERKEN

Merk	LOCTITE
N° Ean13	3616060815477
Type	COLLAGE RIGIDE EPOXY ACRYLIQUE
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE