

## Zelfklevend

# EA-9489-B-1KG-LOCTITE - EA-9489-B-1KG-LOCTITE

<https://www.123kogellager.be/lijm-smering/lijm/zelfklevend/ea-9489-b-1kg-loctite>

TITRE	Epoxy
DESCRIPTION	Partie B, souple, ratio 1/1, multi-usages
NOM	LOCTITE EA 9489 B
CONDITIONNEMENT	10 x 1 kg
DANGEROUS GOODS	Yes
COMMENTAIRE	-
APPROBATION	-

**Description**

LOCTITE® EA 9484 is a 2-part, tough, medium viscosity, industrial grade epoxy adhesive in a 50 ml dual cartridge. Once mixed, the epoxy cures at room temperature to form a flexible gray bonding with medium work life. It can be used for repairing epoxy gas-sealing seams on fiberglass components, repairing printed circuit boards, bonding stainless steel inserts and rubber hose to steel tubing.

**Avantages**

Excellent resistance to shock and impact  
Fully cured epoxy is resistant to a wide range of chemicals and solvents and acts as an excellent electrical insulator  
Suitable for low-stress, high-impact bonding applications of dissimilar materials

**Caractéristiques**

2-part, tough, medium viscosity, industrial grade epoxy adhesive in a 50 ml dual cartridge.

## PRODUCTKENMERKEN

Merk	LOCTITE
N° Ean13	3616060815897
Type	COLLAGE RIGIDE EPOXY ACRYLIQUE
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE