


Lagerblok 2 bevestigingen P2BSS-40M-YTPSS-SKF - P2BSS-40M-YTPSS-SKF

<https://www.123kogellager.be/kogellager-behuizing/lagerbloken/lagerblok-2/p2bss-40m-ytpss-skf>

| Données de calcul | | | |
|---|----------------|-------|------------------|
| Charge dynamique de base | C | 24.7 | kN |
| Charge statique de base | C ₀ | 19 | kN |
| Limite de fatigue | P ₀ | 0.8 | kN |
| Vitesse limite | | 2800 | tr/min |
| Compliance with standard | | | Not standardized |
| Matériau | | | Stainless steel |
| Sealing solution | | | Gutter seals |
| Dimensions | | | |
|  | | | |
| D | | 40 | mm |
| D ₁ | | 51.8 | mm |
| D ₂ | | 48 | mm |
| A | | 30 | mm |
| A ₁ | | 21.5 | mm |
| B | | 49.2 | mm |
| B ₁ | | 10 | mm |
| H | | 90 | mm |
| H ₁ | | 49.2 | mm |
| H ₂ | | 19 | mm |
| J | | 135.5 | mm |
| J | max. | 146 | mm |
| J | min. | 125 | mm |
| L | | 174.5 | mm |
| N | | 24.5 | mm |
| N ₁ | | 14.5 | mm |
| S ₁ | | 30.2 | mm |
| Plots de centrage | | | |
| G | | 12 | mm |
| G | | 0.6 | in |

PRODUCTKENMERKEN

| | |
|-------------------------------|-----------------------|
| Merk | SKF |
| N° Ean13 | 3616060837707 |
| Schachtdiameter | 40 mm |
| Aantal bevestigingsmiddelen | 2 |
| Aanscherping | Excentrische borgring |
| Bevestigingsmiddelpuntafstand | 135.5 mm |
| Materiaal | ROESTVRIJ STAAL |
| Gewicht | 1990 g |
| Verpakking | 1 |
| Standaard | Geen standaard |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE