

# Kegelager 322-22-R-JTEKT - 322-22-R-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegelager/322-22-r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
22	50	19.25	18	15	1	1	36.8	41.6	8 100	11 000	322/22R			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	14.0	27.5	29	44.5	41	46	2	4	1	1	0.37	1.00	0.88	0.178

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952400433
Binnendiameter	22 mm
Buitendiameter	50 mm
Dikte	19.25 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE