

Kegellager 302-32-R-JTEKT - 302-32-R-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/302-32-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|--|--------------------|--------------------------|----------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|-------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | | | | |
| 32 | 65 | 18.25 | 17 | 15 | 1 | 1 | 48.0 | 51.4 | 6 200 | 8 200 | 302/32R | | | |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| — | 14.9 | 37.5 | 39 | 59.5 | 55 | 61 | 3 | 3 | 1 | 1 | 0.37 | 1.60 | 0.88 | 0.266 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952400785 |
| Binnendiameter | 32 mm |
| Buitendiameter | 65 mm |
| Dikte | 18.25 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE