

# Kegellager 32922-JR-JTEKT - 32922-JR-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/32922-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
110	150	25	25	20	129	231	2 300	3 000	<b>32922JR</b>					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
20C	26.3	119	118	141	138	145	5	5	1.5	1.5	0.96	1.69	0.93	1.28

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250125645
Binnendiameter	110 mm
Buitendiameter	150 mm
Dikte	25 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE