

Kegellager 32222-JR-JTEKT - 32222-JR-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/32222-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
110	200	56	53	48	3	2.5	438	640	1 900	2 500	32222JR			
Dimension series to ISO995 (Refer.)	Load center (mm)	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{3a} min.	r _{3a} max.		Y ₁
3FG	46.7	124	126	188	170	190	6	10	2.5	2	0.42	1.43	0.79	7.45

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250124730
Binnendiameter	110 mm
Binnendiameter	4.331" inch
Buitendiameter	200 mm
Buitendiameter	7.874" inch
Dikte	56 mm
Dikte	2.205" inch
Gewicht	7154 g
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE