


Kegellager 32248-JTEKT - 32248-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/32248-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
240	440	127	120	100	5	4	1530	2480	740	980	32248

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	106.1	262	282	422	365	415	16	14	4	3	0.43	1.39	0.77	76.4

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952421735
Binnendiameter	240 mm
Binnendiameter	9.449" inch
Buitendiameter	440 mm
Buitendiameter	17.323" inch
Dikte	127 mm
Dikte	5" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE