


# Kegelager 1755-1729-JTEKT - 1755-1729-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/1755-1729-jtekt>

Single-row tapered roller bearings  
inch series



**Koyo**

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i>	<i>r<sub>b</sub></i>	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.
22.225	56.896	19.368	19.837	19.875	1.2	1.2	40.0	43.1	7 600	10 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
1755	1729	12.5	29.0	27.5	49.0	51.0	1.2	1.2	0.31	1.95	1.07	0.150	0.100

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952425504
Binnendiameter	22.225 mm
Buitendiameter	56.896 mm
Dikte	19.368 mm
Gewicht	264 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE