

## Naaldhulslager 8MKM1210-JTEKT - 8MKM1210-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/8mkm1210-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
8	12	10	8.4	3.25	3.85	37 000	8MKM1210

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	7.991	8.000	11.977	11.995	3.6	4.1

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952469300
Binnendiameter	8 mm
Binnendiameter	0.315" inch
Buitendiameter	12 mm
Buitendiameter	0.472" inch
Dikte	10 mm
Dikte	0.394" inch
Gewicht	4.1 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE