

Naaldhulslager 8MM1210-JTEKT - 8MM1210-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/8mm1210-jtekt>

Drawn cup needle roller bearings 

Full complement type
With closed end



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|---|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 8 | 12 | 10 | 7.8 | 4.95 | 7.50 | 13 000 | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|-------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| | 8MM1210 | 7.991 | 8.000 | 11.977 | 11.995 | 3.7 | 4.2 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952469324 |
| Binnendiameter | 8 mm |
| Buitendiameter | 12 mm |
| Dikte | 10 mm |
| Gewicht | 4.2 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE