

Naaldhulslager BHTM810-JTEKT - BHTM810-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm810-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type With open ends With closed end
8	15	10	8.4	4.00	3.30	34 000	BHTM810

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	Shaft dia. (H6) max.	Housing bore dia. (N7) min.	Housing bore dia. (N7) max.	With open ends	With closed end
—	—	7.991	8.000	14.977	14.995	6.5	7.3

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952469348
Binnendiameter	8 mm
Buitendiameter	15 mm
Dikte	10 mm
Gewicht	6.5 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE