

Naaldhulslager BHTM1220-JTEKT - BHTM1220-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm1220-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|---|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 12 | 19 | 20 | 17.3 | 12.1 | 14.9 | 26 000 | BHTM1220 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| — | — | 11.989 | 12.000 | 18.972 | 18.993 | 17 | 19 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952469782 |
| Binnendiameter | 12 mm |
| Binnendiameter | 0.472" inch |
| Buitendiameter | 19 mm |
| Buitendiameter | 0.748" inch |
| Dikte | 20 mm |
| Dikte | 0.787" inch |
| Gewicht | 17 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE