

## Naaldhulslager BHTM1416-JTEKT - BHTM1416-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm1416-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) |     |     | Basic load ratings (kN) |       | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup> |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|---------------------------|
| $F_w$                    | $D$ | $C$ | $b$<br>min.             | $C_0$ | $C_{0e}$                             | Oil lub.                  |
| 14                       | 22  | 16  | 13.3                    | 11.1  | 12.6                                 | 23 000                    |
|                          |     |     |                         |       |                                      | BHTM1416                  |

| Full complement type |                 | Recommended dimensions (mm) |        |                                |        | Refer. Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends       | With closed end | Shaft dia. (f6)<br>min.     | max.   | Housing bore dia. (N7)<br>min. | max.   | With open ends  | With closed end |
| —                    | —               | 13.989                      | 14.000 | 21.972                         | 21.993 | 19              | 21              |

## PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | JTEKT         |
| N° Ean13       | 3663952470016 |
| Binnendiameter | 14 mm         |
| Buitendiameter | 22 mm         |
| Dikte          | 16 mm         |
| Gewicht        | 19 g          |
| Verpakking     | 1             |

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE