

Naaldhulslager BHTM1420-JTEKT - BHTM1420-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm1420-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|---------------------------|
| F_w | D | C | b min. | C_0 | C_{10} | Oil lub. |
| 14 | 22 | 20 | 17.3 | 14.4 | 17.5 | 23 000 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (f6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| — | — | 13.989 | 14.000 | 21.972 | 21.993 | 23 | 26 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952470030 |
| Binnendiameter | 14 mm |
| Buitendiameter | 22 mm |
| Dikte | 20 mm |
| Gewicht | 23 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE