

Naaldhulslager BHTM1510-JTEKT - BHTM1510-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm1510-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type With open ends With closed end
15	22	10	8.4	6.35	6.45	23 000	BHTM1510

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	21.972	21.993	9.9	11

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470184
Binnendiameter	15 mm
Binnendiameter	0.591" inch
Buitendiameter	22 mm
Buitendiameter	0.866" inch
Dikte	10 mm
Dikte	0.394" inch
Gewicht	9.9 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE