


## Naaldhulslager MHKM1520-JTEKT - MHKM1520-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/mhkm1520-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends	With closed end
15	22	20	17.3	14.2	18.8	23 000		<b>MHKM1520</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	21.972	21.993	20	23

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470245
Binnendiameter	15 mm
Buitendiameter	22 mm
Dikte	20 mm
Gewicht	23 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE