


## Naaldhulslager 16BM2212-JTEKT - 16BM2212-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/16bm2212-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$C_{10}$	$C_{90}$	Oil lub.		Caged type	
			min.				With open ends	With closed end
16	22	12	9.6	10.2	17.1	7 700		

Full complement type				Recommended dimensions (mm)				Refer. Mass (g)	
With open ends		With closed end		Shaft dia. (H6)		Housing bore dia. (H7)		With open ends	With closed end
				min.	max.	min.	max.		
<b>16BM2212</b>				15.989	16.000	21.972	21.993	12	14

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250088735
Binnendiameter	16 mm
Buitendiameter	22 mm
Dikte	12 mm
Gewicht	12 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE