

Naaldhulslager 16MKM2212-JTEKT - 16MKM2212-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/16mkm2212-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type	
16	22	12	9.3	7.80	9.80	22 000	With open ends	With closed end
								16MKM2212

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	21.991 ⁴⁾	22.012 ⁴⁾	11	12

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470290
Binnendiameter	16 mm
Buitendiameter	22 mm
Dikte	12 mm
Gewicht	12 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE