

## Naaldhulslager BTM1710-JTEKT - BTM1710-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm1710-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
17	22	10	—	5.05	6.90	21 000	<b>BTM1710</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	16.989	17.000	21.972	21.993	8.2	—

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470412
Binnendiameter	17 mm
Binnendiameter	0.669" inch
Buitendiameter	22 mm
Buitendiameter	0.866" inch
Dikte	10 mm
Dikte	0.394" inch
Gewicht	8.2 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE