

Naaldhulslager BTM172312-JTEKT - BTM172312-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm172312-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|--|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 17 | 23 | 12 | — | 7.85 | 10.2 | 21 000 | BTM172312 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (f6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| — | — | 16.989 | 17.000 | 22.972 | 22.993 | 12 | — |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952470450 |
| Binnendiameter | 17 mm |
| Buitendiameter | 23 mm |
| Dikte | 12 mm |
| Gewicht | 12 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE