


## Naaldhulslager 18MM2412-JTEKT - 18MM2412-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/18mm2412-jtekt>

Drawn cup needle roller bearings 

Full complement type  
With closed end



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
18	24	12	9.6	10.8	19.2	6 900	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6)		Housing bore dia. (H7)		With open ends	With closed end
		min.	max.	min.	max.		
	18MM2412	17.989	18.000	23.972	23.993	17	20

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3616060465337
Binnendiameter	18 mm
Binnendiameter	0.709" inch
Buitendiameter	24 mm
Buitendiameter	0.945" inch
Dikte	12 mm
Dikte	0.472" inch
Gewicht	20 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE