


Naaldhulslager 18BTM2412-JTEKT - 18BTM2412-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/18btm2412-jtekt>

Drawn cup needle roller bearings **Koyo**



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{10}	Oil lub.	Caged type	
							With open ends	With closed end
18	24	12	—	7.90	10.9	20 000	18BTM2412	

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (f6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	17.989	18.000	23.991 ⁽⁴⁾	24.012 ⁽⁴⁾	12	—

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470627
Binnendiameter	18 mm
Buitendiameter	24 mm
Dikte	12 mm
Gewicht	12 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE