

## Naaldhulslager 20MM2612-JTEKT - 20MM2612-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/20mm2612-jtekt>

Drawn cup needle roller bearings 

Full complement type  
With closed end



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>0</sub>	C <sub>0r</sub>	Oil lub.	Caged type With open ends With closed end
20	26	12	9.6	10.8	20.4	6 300	

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
	20MM2612	19.987	20.000	25.972	25.993	15	17

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952470788
Binnendiameter	20 mm
Binnendiameter	0.787" inch
Buitendiameter	26 mm
Buitendiameter	1.024" inch
Dikte	12 mm
Dikte	0.472" inch
Gewicht	17 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE