


## Naaldhulslager MKM2030-JTEKT - MKM2030-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/mkm2030-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.
4	27	30	27.3	25.4	43.8	18 000

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6)		Housing bore dia. (H7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	19.987	20.000	26.972	26.993	40	45

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471013
Binnendiameter	20 mm
Buitendiameter	27 mm
Dikte	30 mm
Gewicht	45 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE