

## Naaldhulslager 22MKM2820-JTEKT - 22MKM2820-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/22mkm2820-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends    With closed end
22	28	20	17.3	14.9	26.5	17 000	<b>22MKM2820</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φd) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	27.972	27.993	25	28

### PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471167
Binnendiameter	22 mm
Binnendiameter	0.866" inch
Buitendiameter	28 mm
Buitendiameter	1.102" inch
Dikte	20 mm
Dikte	0.787" inch
Gewicht	28 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE