

Naaldhulslager BTM2225-JTEKT - BTM2225-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/btm2225-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾	
F_w	D	C	b min.	C_0	C_{10}	Oil lub.	
22	29	25	—	20.4	36.1	16 000	BTM2225

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	28.972	28.993	37	—

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471235
Binnendiameter	22 mm
Binnendiameter	0.866" inch
Buitendiameter	29 mm
Buitendiameter	1.142" inch
Dikte	25 mm
Dikte	0.984" inch
Gewicht	37 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE