

Naaldhulslager MKM2516-JTEKT - MKM2516-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/mkm2516-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|------------------------------|-----------------|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type With open ends | With closed end |
| 25 | 32 | 16 | 13.3 | 15.3 | 24.6 | 14 000 | | MKM2516 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 24.987 | 25.000 | 31.967 | 31.992 | 26 | 30 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952471365 |
| Binnendiameter | 25 mm |
| Buitendiameter | 32 mm |
| Dikte | 16 mm |
| Gewicht | 30 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE