


Naaldhulslager BHTM2520-1-JTEKT - BHTM2520-1-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bhtm2520-1-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type With open ends With closed end
25	33	20	17.3	19.2	29.7	14 000	BHTM2520-1

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.967	32.992	37	41

PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	4549250003165
Binnendiameter	25 mm
Binnendiameter	0.984" inch
Buitendiameter	33 mm
Buitendiameter	1.299" inch
Dikte	20 mm
Dikte	0.787" inch
Gewicht	37 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE