


Naaldhulslager MHKM2616-JTEKT - MHKM2616-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/mhkm2616-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|--|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 26 | 34 | 16 | 13.3 | 15.3 | 22.5 | 14 000 | MHKM2616 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 25.987 | 26.000 | 33.967 | 33.992 | 30 | 34 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | JTEKT |
| N° Ean13 | 3663952471570 |
| Binnendiameter | 26 mm |
| Buitendiameter | 34 mm |
| Dikte | 16 mm |
| Gewicht | 34 g |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE