


## Naaldhulslager MHKM2820-JTEKT - MHKM2820-JTEKT

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/mhkm2820-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
28	37	20	17.3	21.6	33.0	13 000	MHKM2820

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	27.987	28.000	36.967	36.992	46	52

## PRODUCTKENMERKEN

Merk	JTEKT
N° Ean13	3663952471747
Binnendiameter	28 mm
Buitendiameter	37 mm
Dikte	20 mm
Gewicht	52 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE